







Flexible Tressé Textile

Désignation	Code	∅ Int.  DN-Inch-mm	∅ Ext.  mm	Pression Service  Bars	Pression Rupture  Bars	Rayon mini Courbure  mm	Poids  Kg/mt
-------------	------	---	---	---	---	--	---



Flexible 1TE/R6 - EN854 1TE - SAE 100 R6

Recommandé pour ligne basse pression et retour

FLEX. 1TE.04		3	3/16	4,8	15,9	415	1660	90	0,37
FLEX. 1TE.06	238068813	4	1/4	6,4	12,6	28	112	45	0,10
FLEX. 1TE.08	238088828	5	5/16	7,9	14,0	28	112	65	0,13
FLEX. 1TE.10	238108815	6	3/8	9,5	15,8	28	112	75	0,16
FLEX. 1TE.13	238138675	8	1/2	12,8	19,4	28	112	90	0,21
FLEX. 1TE.16	238168813	10	5/8	16,0	23,0	24	96	115	0,27
FLEX. 1TE.19	238198812	12	3/4	19,0	26,0	21	84	150	0,32
FLEX. 1TE.25	238258837	16	1"	25,4	33,0	20	80	205	0,44



TEKNO 1TE/R6

3/8"

(9,5mm)

EN 854 1TE
SAE 100 R6

28 Bar
2,8 MPa

406 Psi







MARKING/MARCATURA: TRANSFER TAPE

OPERATING
TEMPERATURE RANGE:
- 40°C/+100°C
(-40°F to +212°F)

TUBE:
oil resistant synthetic rubber

REINFORCEMENT:
1 high tensile textile braid

COVER:
weather resistant synthetic rubber.

Désignation	Code	∅ Int.  DN-Inch-mm	∅ Ext.  mm	Pression Service  Bars	Pression Rupture  Bars	Rayon mini Courbure  mm	Poids  Kg/mt
-------------	------	---	---	---	---	--	---



Flexible 2TE - EN854 2TE - ISO 4079 - 2TE

Recommandé pour ligne basse pression et retour

FLEX. 2TE.04	238048580	3	3/16	4,8	12,0	80	320	25	0,12
FLEX. 2TE.06	238068826	4	1/4	6,4	13,2	75	300	40	0,13
FLEX. 2TE.08	238088827	5	5/16	7,9	14,8	68	272	50	0,17
FLEX. 2TE.10	238108828	6	3/8	9,5	16,4	63	252	60	0,18
FLEX. 2TE.13	238138829	8	1/2	12,8	20,4	58	232	70	0,26
FLEX. 2TE.16	238168830	10	5/8	16,0	24,0	50	200	90	0,36
FLEX. 2TE.19	238198831	12	3/4	19,0	27,3	45	180	110	0,40
FLEX. 2TE.25	238258832	16	1"	25,4	34,6	40	160	150	0,58
FLEX. 2TE.32	238328833	20	1 1/4	31,8	41,0	35	140	170	0,72



TEKNO 2TE

3/8"

(9,5mm)

EN 854 2TE
ISO 4079-2TE

63 Bar
6,3 MPa

914 Psi

MARKING/MARCATURA: TRANSFER TAPE







OPERATING
TEMPERATURE RANGE:
- 40°C/+100°C
(-40°F to +212°F)

TUBE:
oil resistant synthetic rubber

REINFORCEMENT:
1 high tensile textile braid

COVER:
weather resistant synthetic rubber.




Désignation	Code	Ø Int.  DN-Inch-mm	Ø Ext.  mm	Pression Service  Bars	Pression Rupture  Bars	Rayon mini Courbure  mm	Poids  Kg/mt
-------------	------	---	---	---	---	--	---



Flexible 3TE - EN854 3TE - ISO 4079 - 3TE

Recommandé pour ligne basse et moyenne pression et retour

FLEX. 3TE.04		3	3/16	4,8	12,4	160	640	40	0,12
FLEX. 3TE.06	238068669	4	1/4	6,4	14,8	145	580	45	0,17
FLEX. 3TE.08	238088670	5	5/16	7,9	17,5	130	520	55	0,24
FLEX. 3TE.10	238107671	6	3/8	9,5	19,1	110	440	70	0,25
FLEX. 3TE.13	238138674	8	1/2	12,8	22,3	93	372	85	0,31
FLEX. 3TE.16	238168675	10	5/8	16,0	26,5	80	320	105	0,44
FLEX. 3TE.19	238197676	12	3/4	19,0	29,6	70	280	130	0,51
FLEX. 3TE.25	238258677	16	1"	25,4	36,5	55	220	150	0,67
FLEX. 3TE.32	238328678	20	1"1/4	31,8	42,3	45	180	190	0,79
FLEX. 3TE.40	238408679	24	1"1/2	38,1	49,6	40	160	240	1,05
FLEX. 3TE.50	238508680	32	2"	50,8					

	TEKNO 3TE	3/8"	(9,5mm)	EN 854 3TE ISO 4079 3TE	110 Bar 11 MPa	1595 Psi
---	------------------	-------------	---------	----------------------------	-------------------	-----------------

MARKING/MARCATURA: TRANSFER TAPE

OPERATING TEMPERATURE RANGE:
- 40°C/+100°C
(-40°F to +212°F)

TUBE:
oil resistant synthetic rubber

REINFORCEMENT:
2 high tensile textile braids

COVER:
weather resistant synthetic rubber

